

MTS-A1

Android Total Station



The MTS-A1 features a 6-inch HD touchscreen with Android OS and surveying software, equipped with a high-resolution camera to improve efficiency and accuracy, MTS-A1 offers high-quality, high-accurate and stable performance.

- 6-inch TFT Screen
- AR camera
- Hot-swappable support
- EDM 1000m
- 4GB RAM + 64GB
- Wireless connection
- Type-C
- Android

Precise Visual Stakeout

HD image guidance, with real-time image guidance, locate points effortlessly, rapidly, and accurately—making staking simpler and more efficient than ever.

CAD Stakeout

Powered by a high-performance CAD engine, lightning-fast drawing loading. Experience dynamically precise, visible staking—truly achieving What you design is what you see; what you see is what you get measured.

M-survey Software Operation

Command your total station from your palm. Replace complex instrument logic with intuitive mobile control, power lines and more. Data auto-saves to mobile devices, seamlessly bridging field and office workflows.

Hot-swappable Battery system

Zero downtime power transition, featuring an integrated buffer battery and dual-battery control system, achieve uninterrupted operation during battery swaps, empowering continuous measurement without interruption.



APPLICATION:



Bridge



construction



Mining



Tunnel



Railway



Road

SPECIFICATIONS:

Angle Measurement	Accuracy	1" / 2" (Optional)
	Reading System	Absolute, continuous four-quadrant
	Display Resolution	0.1" / 1"
Telescope	Magnification	30x
	Field Of View	1° 30'
	Minimum Focus Distance	1.7m
	Resolution	0'
Tilt Compensation	Pointer	Red laser dot
	System	Dual axis
	Working Range	±4'
Distance Measurement Range	Resolution	1"
	Single Prism Mode	4000m
	Reflector	2000m
Distance Measurement Accuracy	Non-Prism Mode	1000m
	Standard Prism Mode	±1 mm + 1 ppm
Measurement Time	Reflectorless & Non-Prism	D < 500 m: ±2 mm + 2 ppm D > 500 m: ±3 mm + 2 ppm
	Standard Prism Mode (Tracking/Precise)	0.1 / 0.3 sec
	Reflectorless	Fine: 0.7s Rapid: 0.5s Tracking: 0.3s
Level Vial Sensitivity	Tube Level	30" / 2 mm
	Circular Level	8' / 2 mm
Laser Plummet	Laser Type	Red laser dot, 635 nm
	Accuracy	1.5 mm (Instrument Height 1.5 m)
Android Configuration	Android Platform	MediaTek G81, 4GB DDR4x + 64GB eMMC
	Display Screen	6 inch Touch Screen: 2* 1280*720 (16:9)
Communication	Interface	1* Nano sim card, 1* T card, Type-C(OTG), 1* USB2.0, 1* USB
	Wireless	Bluetooth 5.0, wifi, GPS GLONASS, BDS, Galileo
Environmental	Operating Temperature	-20°C - 55°C
	Storage Temperature	-30°C - 55°C
	Waterproof/Dustproof	IP65
Electrical	Battery Voltage/Capacity/Type	Li-ion rechargeable battery, 7.2V, 7000mAh
	Stakeout Camera	8 MP AR camera
Physical	Dimensions	217 x 198 x 378 mm, 7kg

*The above technical parameters are for your reference. The company reserves the right to change the design and planning of the product based on the actual product.

